# MioCARE

# Pocket sized tablet computer designed for healthcare



# **Unified Communication**

3G, WIFI and Bluetooth® 4.0 connected.

# IP54 Rugged and Cleanable

Water, dust, 1 meter drop resistant and anti-microbial.

## Open & Flexible

Uses Android™ 4.2. with SDK and emulator support.

# Integrated Data capture

NFC, HF RFID and 2D barcode built into workflows.



2D Barcode Reader

# Introducing the new 5.88" touch screen tablet from MioCARE with 3G and WIFI.

The A335 includes integrated NFC and a 2D barcode scanner offering data capture built right into your workflow. This gives real-time and context aware reporting and data retrieval offering significant error reduction. Integrated AGPS adds location awareness.

With 3G and WiFi connectivity the MioCARE A335 is always connected indoors and out. The cradles designed for healthcare are fast charging and allow the A335 to be always available.



#### **Unified Communication**

3G, WiFi and Bluetooth® 4.0. connected.

## IP54 Rugged and Cleanable

Water, dust, 1 meter drop resistant and anit-microbial

## Open & Flexible

Uses Android™ 4.2 with SDK and Emulator support.

#### Integrated Data capture

NFC, HF RFID and 2D barcodes built into workflows.

# Pocket sized tablet computer designed for healthcare





#### Package contents:

- Device
- AC mains charger
- USB to Mini USB cable
- Printed quick start guide
- Printed warranty & end user license agreement

#### System

Screen: 5.88" Capacitive, WVGA (800 x 480), 350 nits

OS: Android™ 4.2 Processor: TI OMAP4470 1.5GHz Location: UBlox U200 A-GPS

**Battery:** 3000mAh capacity, up to 6 hours operation,

charge via mini USB

RAM: 1GB

Memory: Internal 16GB

Expandable: MicroSD SDHC up to 32GB
Connectivity: 3G, Wireless 802.11 a/b/g/n (2.4 & 5GHz),

Bluetooth® 4.0

Input: Mini USB, Micro HD Interface
Sensors: 2D barcode imager, Accelerometer
Near field communication (NFC), GPS

**Environment**: IP54, 1M drop resistant

Camera: Rear 5.0Mp AF / Front 1.2Mp FF
Audio: Mono speaker, 3.5mm jack, microphone

AC mains: In: 100~240VAC Out: 5VDC, 2A Mini USB

Operating

temperature: -10 to +50°C (Camera function: -10 to +45°C)

Certification: CE/CB - CE (R&TTE), FCC, NCC/BSMI, CCC,

IP54, EN60601\*, Cisco CCX\*

Warranty: 12 months (extended warranty available)

**Dimensions:** 200 (h) x 99 (w) x 15mm (d)

Weight: 370g

\* Optional

