Honeywell

PRELIMINARY

Granit 1911i

Wireless Industrial-Grade Area-Imaging

The Granit[™] 1911i wireless industrial-grade area-imaging scanner is designed to withstand the varied demands that exist in harsh working environments. Featuring a custom built housing that is redefining the standard for scanner reliability, the IP65 rated Granit 1911i is built to survive 5,000 3.3 (1 m) tumbles and 50 drops to concrete from 6.5 (2 m) even at -23°F (-30°C). As a result, businesses can expect to experience minimal device downtime and a lower overall cost of ownership.

Powered by Honeywell's Adaptus[™] 6.0 imaging technology and its revolutionary decoding architecture, the Granit 1911i provides users with the same exceptional bar code reading performance as the best-in-class Xenon[™] series of area-imaging scanners. From poorly printed and damaged codes to low density linear codes, the Granit 1911i is built to read virtually all bar codes with ease—supporting maximum operator productivity with its enhanced illumination, crisp laser aiming and extended depth-of-field.

The Granit 1911i also incorporates a Bluetooth[®] Class 1, v2.1 radio, enabling wireless connectivity and unrestricted movement up to 300 feet (100 m) from the base. Additionally, with Honeywell's Shift-PLUS power management system users can expect up to 14 hours of battery life reducing the cost associated with battery backups and replacements. A paging system is also available for added convenience to assist with locating misplaced scanners.

Created specifically for applications in which high performance scanning is expected and durability is highly valued, the Granit 1911i is the optimal solution for businesses operating in unpredictable conditions.



Features

- Class-Leading Durability: The custom-built IP65-rated housing is able to withstand 5,000 3.3 (1 m) tumbles and survive 50 drops from 6.5 (2 m) at -23°F (-30°C) reducing service costs and increasing device uptime
- Wireless Connectivity: Bluetooth[®] Class 1, v2.1 radio enables movement up to 300[°] (100 m) from base, and reduces interference with other wireless systems. Up to 7 imagers can communicate with a single base, reducing the total cost of ownership
- **TotalFreedom[™] 2.0:** The second-generation of Honeywell's area-imaging development platform enables the loading and linking of multiple applications to enhance image decoding, data formatting and image processing—eliminating the need for host system modifications
- Long-Lasting Lithium-Ion Battery: Powers up to 50,000 scans per full charge and is removable without tools ensuring maximum uptime for operations running multiple shifts
- Extended Linear Depth of Field: Scans out-of-reach items with ease and allows users to scan 20 mil linear codes from up to 22" (56 cm) without sacrificing performance on 2D codes
- Remote MasterMind[™] Scanning Management Software: Quick and convenient solution for IT administrators seeking to manage the scanners within their network from a single remote location

Granit 1911i Technical Specifications

Wireless		
Radio/Range	2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1: Class 1: 100m (300') line of sight	
Data Rate (Transmission Rate)	Up to 1 Mbits/S	
Battery	2000 mAh Li-ion minimum	
Number of Scans	Up to 50,000 scans per charge	
Expected Hours of Operation	14 hours	
Expected Charge Time*	4.5 hours	
Mechanical/Electrical		
	Scanner (1911iER-3)	Charger/Communication Base (COB02/CCB02-100BT-07N)
Dimensions (LxWxH)	133 mm x 75 mm x 195 mm (5.2″ x 2.9″ x 7.6″)	250 mm x 103 mm x 65 mm (9.9″ x 4.1″ x 2.6″)
Weight	362 g (12.8 oz)	283 g (10.0 oz)
Operating Power (Charging)	N/A	5 W (1A @ 5 V)
Non-Charging Power	N/A	0.5 W (0.1A @ 5 V)
Host System Interfaces	N/A	USB, Keyboard Wedge, RS232
Environmental		
	Scanner (1911iER-3)	Charger/Communication Base (COB02/CCB02-100BT-07N)
Operating Temperature**	-20°C to 50°C (-4°F to 122°F)	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)	-40°C to 70°C (-40°F to 158°F)
Humidity	Up to 95% relative humidity, non-condensing	Up to 95% relative humidity, non-condensing
Drop	Designed to withstand 50 2 m (6.5') drops to concrete at -20°C	Designed to withstand 50 1.2 m (4') drops to concrete at -20°C
Tumble	5,000 1m (40 [°]) tumbles	5,000 1m (40") tumbles
Environmental Sealing	IP65	IP51
Light Levels	0 to 100,000 lux (9,290 foot-candles)	N/A
ESD	$\pm 20 Kv$ air discharge, $\pm 8 kV$ contact discharge	±20Kv air discharge, ±8kV contact discharge
Scan Performance		
Scan Pattern	Area Imager (838 x 640 pixel array)	
Motion Tolerance	Up to 610 cm/s (240 in/s) for 13 mil UPC at optimal focus	
Scan Angle	ER Focus: Horizontal: 31.6°; Vertical: 24.4°	
Symbol Contrast	20% minimum reflectance difference	
Pitch, Skew	45°, 65°	
Warranty	3 year factory warranty (Note: battery warranty is 1 year	r)

*battery charging only occurs between 5° C and 40°C; **with industrial grade cable ordered separately

For a complete listing of all compliance approvals and certifications, please visit www.honeywellaidc.com/compliance

For a complete listing of all supported bar code symbologies, please visit www.honeywellaidc.com/symbologies



For more information: www.honeywellaidc.com

Honeywell Scanning & Mobility

9680 Old Bailes Road Fort Mill, SC 29707 800.582.4263 www.honeywell.com

Typical Performance*	Extended Range (ER)		
Narrow Width			
7.5 mil Code 39	58 mm - 287 mm (2.3″ - 11.3″)		
13 mil UPC	36 mm - 442 mm (1.4" - 17.4")		
20 mil Code 39	30 mm - 561 mm (1.2" - 22.1")		
6.7 mil PDF417	84 mm - 206 mm (3.3" - 8.1")		
10 mil DM**	86 mm - 208 mm (3.4" - 8.2")		
20 mil QR	25 mm - 394 mm (1.0" - 15.5")		
Resolution 1D Code 39	5 mil (0.127 mm)		
Resolution 2D DM**	7.5 mil (0.191 mm)		
*Performance may be impacted by bar code quality and			

environmental conditions **Data Matrix (DM)



1911i-DS Rev A 09/12 ©2012 Honeywell International Inc.



About BarcodesInc

Who We Are

We Owe Our Success To You

Why Choose BarcodesInc?

Dedicated Account A UbU[Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same A 2

Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service & at È

Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BarcodesInc 200 West Monroe Street Chicago, Illinois 60606

Phone: 1-800-351-9962 Fax: 1-312-212-1800 www.barcodesinc.com

BRANDS





Intermec

Honeywell

ODATALOGIC











unitech



Microsoft



<u>symbol</u>' AND MORE